CLASS TEST						S.No. : 02_SP_ME_A_17032023			
TRADE EASS India's Best Institute for IES, GATE & PSUs									
Delhi Bhopal Hyderabad Jaipur Lucknow Pune Bhubaneswar Kolkata									
		M			с т/				
MECHANICAL ENGINEERING									
	Date of Test : 17/03/2023								
AN	SWER KEY	>							
1.	(b)	7.	(b)	13.	(b)	19.	(b)	25.	(a)
2.	(a)	8.	(a)	14.	(b)	20.	(a)	26.	(a)
3.	(b)	9.	(c)	15.	(a)	21.	(c)	27.	(d)
4.	(a)	10.	(b)	16.	(d)	22.	(c)	28.	(c)
5.	(a)	11.	(a)	17.	(d)	23.	(b)	29.	(d)
6.	(c)	12.	(d)	18.	(c)	24.	(a)	30.	(a)



DETAILED EXPLANATIONS

1. (b)

Mixture of abrasive and carrier gas will come out from the nozzle

$$Q = A \times v$$
$$= \frac{\pi}{4} \times (0.1)^2 \times 200 \times 100$$
$$= 157.08 \text{ cm}^3/\text{s}$$

2. (a)

Cone height =
$$\frac{D/2}{\tan \frac{\alpha}{2}} = \frac{5}{\tan 60^\circ} = 2.886 \text{ mm}$$

3. (b)

cutting velocity,
$$(V) = \frac{\pi dN}{1000}$$

 $71.5 = \frac{\pi d \times 350}{1000}$
diameter $(d) = 65.026$ mm

4. (a)

In USM the variation of material removal rate (MRR) with respect to the volume concentration of abrasive in water slurry is governed by:



Volume concentration of abrasive slurry, C

5. (a)

A negative rake angle always leads to higher cutting force than what is produced with a cutting point having positive rake angle. This further illustrates that at low grinding velocity this difference in grinding force is more pronounced. It is interesting to note that the difference is narrowed at a high grinding velocity and the grinding force becomes virtually independent to the rake angle. This is one of the reasons of conducting grinding at a very high velocity in order to minimize the influence of negative rake angle.

6. (c)

Axial feed,
$$F = \frac{3000 \text{ mm}}{30s} = 100 \text{ mm/s} = 6000 \text{ mm/min}$$

We know, Axial feed, $F = \pi dN \sin\theta$ $6000 = \pi \times 200 \times 500 \times \sin\theta$ $\theta = 1.094^{\circ} \simeq 1.09^{\circ}$

7. (b)

- 1. EDM has the lowest specific power requirement and can achieve sufficient accuracy.
- 2. ECM has the highest metal removal rate.
- 3. USM and AJM have low MRR and combined with high tool wear, are used for non-metal cutting
- 4. LBM and EBM have high penetration rates with low MRR and, therefore, are commonly used for micro drilling, sheet cutting.

8. (a)

USM is used for machining of hard, brittle and non-conductive materials.

9. (c)

Glazing is the phenomenon in which the grinding wheel becomes dull due to wearing out of sharp edges of grit on continuous machining.

10. (b)

$$V = \frac{NL(1+m)}{1000} = \frac{20 \times 300 \left(1 + \frac{3}{4}\right)}{1000} = 10.5 \text{ m/min}$$

11. (a)

Given : Depth (d) = 5 mm, $f_m = 2 \text{ mm/s}$ Width of cut = Diameter of the tool $\Rightarrow \qquad w = 40 \text{ mm}$ Material removal rate (MRR) = wdf_m = $40 \times 5 \times 2 = 400 \text{ mm}^3/\text{s}$ Power required = $\frac{(\text{Specific energy}) \times MRR}{\eta} = \frac{8.5 \times 400}{0.5}$ = 6.8 kW

12. (d)

Time taken for cutting,

$$t = \frac{L}{V_c} = \frac{150 \times 60}{200} = 45 \text{ sec}$$

13. (b)

Total material removal rate,

$$MRR = \frac{\pi}{4}D_1^2 f_m + \frac{\pi}{4}D_2^2 f_m$$

$$= \frac{\pi}{4}f_m (D_1^2 + D_2^2)$$

$$\Rightarrow \qquad \frac{\pi}{4} \times (13^2 + 19^2) \times f_m = 24580$$

$$f_m = 59.049 \text{ mm/min}$$
Compulsory approach for drill 1, $x_1 = \frac{D_1/2}{\tan \frac{\alpha}{2}} = \frac{13/2}{\tan 59^\circ} = 3.905 \text{ mm}$
Compulsory approach for drill 2, $x_2 = \frac{D_2/2}{\tan \frac{\alpha}{2}} = \frac{19/2}{\tan 59^\circ} = 5.708 \text{ mm}$
Time required to drill hole 1 = $\frac{L + x_1}{f_m} = \frac{40 + 3.905}{59.049} \times 60 = 44.612 \text{ seconds}$
Time required to drill hole 2 = $\frac{L + x_2}{f_m} = \frac{40 + 5.708}{59.049} \times 60 = 46.44 \text{ seconds}$
As both the drills are working simultaneously, so the time for the complete

As both the drills are working simultaneously, so the time for the complete operation is 46.44 seconds.

14. (b)



© Copyright: MADE EASY

15. (a)

We know, MRR is given by,

$$MRR = \frac{AI}{\rho VF}$$
So,

$$I = \frac{(MRR) \times \rho VF}{A}$$

$$\therefore \qquad I = \frac{(2.5/60) \times 8 \times 2 \times 96500}{56} = 1148.81 \text{ Amp.}$$

16. (d)

In AJM process, the MRR is proportional to, MRR $\propto Od^3$

where,

$$Q = \text{Flow rate of abrasives}$$

$$d = \text{mean diameter}$$
So,

$$\frac{10}{MRR'} = \frac{Qd^3}{2Q \times (d/2)^3}$$

$$MRR' = 10 \times \frac{2}{8} = 2.5 \text{ mm}^3/\text{s}$$

17. (d)

$$V_{c} = \frac{\pi DN}{1000}$$

$$\Rightarrow \qquad N = \frac{1000 \times 5}{\pi \times 50} = 31.83 \text{ rpm}$$
Now,
$$T_{c} = \frac{L_{c}}{fN} \times \text{Number of passes}$$

$$= \frac{150}{1 \times 31.83} \times 3 = 14.14 \text{ minutes}$$

18. (c)

19. (b)

$$MRR = \frac{\pi}{4}D^{2}fN$$

$$D = 25 \text{ mm} \qquad f = 0.25 \text{ mm/rev}$$

$$V = \frac{\pi DN}{1000}$$

$$30 = \frac{\pi \times 25 \times N}{1000}$$

$$N = 381.972 \text{ rpm}$$

$$MRR = \frac{\pi}{4} \times 25^{2} \times 0.25 \times 381.972 \text{ mm}^{3}/\text{ min}$$

$$= 46874.9 \text{ mm}^{3}/\text{min} = 0.78 \text{ cm}^{3}/\text{sec}$$

 \Rightarrow



$$V = \frac{1000}{1000} = \frac{1000}{1000} = 21.99 \text{ m},$$

$$P = \frac{1600 \times 3 \times 1 \times 21.99}{60}$$

$$P = 1.76 \text{ kW}$$

23. (b)

$$Fine/cut = \frac{Number of double strokes \times time}{double stroke}$$
$$= \frac{B}{f} \times \frac{1}{10} = \frac{300}{0.2} \times \frac{1}{10} = 150 \text{ min}$$

24. (a)

 $\begin{array}{l} \mbox{Chemical machining} \rightarrow \mbox{Corrosive reaction} \\ \mbox{Electro-chemical machining} \rightarrow \mbox{Ion displacement} \\ \mbox{Electro discharge machining} \rightarrow \mbox{Fusion and vaporization} \\ \mbox{Ultrasonic machining} \rightarrow \mbox{Erosion} \end{array}$

25. (a)

$$t_1 = \frac{2f}{Nz} \sqrt{\frac{d}{D}}$$
$$t_2 = \frac{2f}{Nz} \sqrt{\frac{3d}{3D}}$$
% change $t_2 - t_1 = 0$

∴ % cl

26. (a)

Given: $N_{\min} = 35 \text{ rpm}$ $N_{\max} = 300 \text{ rpm}$ n = 6Sped, ratio, $r = {n-1}\sqrt{\frac{N_{\max}}{N_{\min}}} = \sqrt[5]{\frac{300}{35}} = 1.537$ 3^{rd} spindle speed, $N_3 = N_1 r^2$ $= 35(1.537)^2 = 82.66 \text{ rpm}$

27. (d)

Given, Z = 10 N = 100 rpm f = 50 mm/minFeed per revolution, $f_N = \frac{50}{100} = 0.5 \text{ mm/rev}.$ Feed per tooth, $f_Z = \frac{f_N}{Z} = \frac{0.5}{10} = 0.05 \text{ mm/tooth}$

29. (d)

Given : $N_s = 200$ rpm, $D_s = 1$ mm, $Z_s = 2$, $p_L = 4$ mm $N_S \times p_S \times Z_S = N_L \times p_L \times Z_L \times 4$ $200 \times 1 \times 2 = N_L \times 4$ $N_L = 100$ rpm